



subject: **Enhancements to dmeas connection** command.

date: **March 20, 2001**

from: **BNS-2000 Customer Support  
1800WE2CARE**

*PRODUCT DOCUMENTATION NOTICE*

This memo describes additions made to the **dmeas connection** command in BNS-2000 Release 5.0.

The **dmeas connection** command now displays two additional fields, namely **AVERAGE** and **CURRENTLY ACTIVE CALLS**.

Sample output for these new options follows immediately below:

CC0> dmeas conn h

01-03-20 22:03:08 NODE=pluto  
M CONNECTION MEASUREMENTS 01-03-20 22:00 ----> 01-03-20 22:03

TOTAL OF HELD CALLS: 0 PEAK HELD CALLS: 0

GROUP	PEAK	CONN	ATT	FAILURES	CONTENTION	SECURITY	OTHER
trkgrp	2( 0%)	0	0( 0%)	0( 0%)	0( 0%)	0( 0%)	
-----							
NODE:	4	0	0( 0%)	0( 0%)	0( 0%)	0( 0%)	
RECEIVED	2	0	0( 0%)				

AVERAGE over 188 seconds: 0.00/sec ATTEMPTS, 0.00/sec FAIL, 0.00/sec SUCCEED  
2 CURRENTLY ACTIVE CALLS

01-03-20 22:03:08 NODE=pluto  
M CONNECTION MEASUREMENTS 01-03-20 22:00 ----> 01-03-20 22:03

<----- SECURITY ANALYSIS ----->  
GROUP ORIG GRP CUG CALL SCR CHK TRAF AGR  
no security failures